



Deze download wordt u aangeboden door **Pick-upnaalden.nl**

Fazantendreef 17-19

8251 JR Dronten

T: 0321 769022

E: info@pick-upnaalden.nl

W: www.pickupnaalden.com

W: www.pickupnaald.com

Facebook: www.facebook.com/pickupnaalden

Twitter: twitter.com/Pickupnaalden

Google+ : plus.google.com/114738445546162436900



Main Features

■ Refined External Design

The DP-300F's 4mm-thick cabinet wall that offers both strength and high density has been beautifully finished with a gloss coating. The straight tone arm and aluminum diecast turntable have been formed in a slim, textually attractive design. With a body width of 434mm, it combines very elegantly with full-size system components.

■ Fully Automatic Player

When the 30cm or 17cm record size is selected, with a simple operation the tone arm automatically moves and plays the record and then returns when playback ends. Different cartridges can be used as desired, and since fine adjustments can also be made for anti-skating and zero balance, ideal conditions for playing a record can be achieved.

■ Straight Tone Arm

The DP-300F's straight tone arm brings out the maximum performance of cartridges with superior tracing capabilities. The supplied cartridge can be replaced with a variety of commercially available cartridges. (Compatible cartridge weight: 5.0 - 10.0 g)

■ Includes High-grade MM Cartridge

■ Diecast Aluminum Turntable

The DP-300F's turntable has been constructed of diecast aluminum to achieve high inertial mass for stable rotation. The vibration-resistant turntable sheet is about 5mm thick and uses hologram vibration analysis to improve its ability to hold a record.

■ Built-in PHONO Equalizer

Since the DP-300F includes a built-in PHONO equalizer, it can be connected directly to a mini component or integrated amp that does not have a PHONO terminal. (ON/OFF switchable)

■ Manual Arm Lifter

The DP-300F is also equipped with an arm lifter mechanism to facilitate manual operation. The arm lifter makes it easy to place or remove the needle from any location on the record.

Specifications

Motor Section

Drive system	Belt drive
Speed	33 1/3, 45 rpm
Wow & flutter	0.10% (WRMS)
Turntable	Diecast aluminum

Tone arm

Type	Straight
Effective length	221.5 mm, 8.72 inch
Overhang	19 mm, 0.75 inch
Tracking error	Within 3°
Stylus pressure range	0 - 4.0g (0.1g increments)
Compatible cartridge weight	5.0 - 10.0g (excluding headshell)

Cartridge

Type	MM
Appropriate needle pressure	2.0g
Cartridge weight	5g
Replacement needle	DSN-85
Supplied headshell weight	10g

(Can be replaced with dedicated shell:
PCL-310SP [Premium Silver] or PCL-310K [Black])

General

Power supply	AC 120V, 60 Hz
Power consumption	2W
Dimensions	434 (W) x 122 (H) x 381 (D) mm 17.1 (W) x 4.8 (H) x 15.0 (D) inch (including feet)
Weight	5.5 kg, 12.13 lbs

*Design and specifications are subject to change without notice.