



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : [www.pickupnaalden.com](http://www.pickupnaalden.com)  
Email : [info@pick-upnaalden.nl](mailto:info@pick-upnaalden.nl)  
Facebook : [www.facebook.com/pickupnaalden](http://www.facebook.com/pickupnaalden)  
Twitter : [twitter.com/Pickupnaalden](http://twitter.com/Pickupnaalden)  
Google+ : [https://plus.google.com/+FCaris\\_pickupnaalden](https://plus.google.com/+FCaris_pickupnaalden)

# KD-2033



## SPECIFICATIONS

### MOTOR and TURNTABLE

Drive System	Belt drive system
Motor	4-pole synchronous motor
Turntable Platter	12 inch (30 cm) diameter aluminum alloy diecast
Speeds	2 speeds, 33-1/3 and 45 rpm.
Wow and Flutter	Less than 0.06% (WRMS)
Signal to Noise	More than 49 dB

### TONEARM

Type	Static-balance type, S-shaped pipe arm EIA plug-inconnector
Effective Arm Length	8-7/16 inch (215 mm)
Over-Hang	3/8 inch (9.5 mm)
Tracking Error	±1.5 degree
Stylus Pressure	
Variable Range	0 to 4 grams
Usable Cartridge Weight	4 to 10 grams

### CARTRIDGE (Only for U,X,M type)

Type	Moving magnet type (V-39MKII)
Frequency Response	20~20,000 Hz
Channel Separation	More than 25 dB (at 1000 Hz)
Output Voltage	3 mV (5 cm/sec at 1,000 Hz)
Output Balance	1.5 dB (5 cm/sec at 1,000 Hz)
Load Impedance	50 k ohms
Stylus	0.5 mil diamond
Stylus Pressure	2±0.25 grams
Compliance	7 × 10 <sup>-6</sup> cm/dyne

### SPECIAL MECHANISM

(Additional Feature)	Auto-return Auto-cut Pause elevation (variable speed) Return speed adjusting mechanism Anti-skating device Stylus pressure direct- readout counter Insulator Free-stop action dust cover
----------------------	--

### ACCESSORIES

(Supplied)	EP adapter Motor lubricating oil Over-hang gauge Motor pulley and screw driver (only for M.U.W type)
------------	--

### POWER

### CONSUMPTION

11 watts

### DIMENSIONS

W 18-7/8 inch (480 mm)  
D 14-7/16 inch (367 mm)  
H 6-7/8 inch (175 mm)

### WEIGHT

13.2 lbs (6 kg)

### POWER

### REQUIREMENT

AC 120V, 60 Hz (K.P. type)  
AC 220V, 50 Hz (L type)  
AC 220V~240V, 50 Hz  
(T.X.S type)  
AC 110~120/220~240V,  
50/60 Hz (M.U.W type)