



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : www.pickupnaalden.com
Email : info@pick-upnaalden.nl
Facebook : www.facebook.com/pickupnaalden
Twitter : twitter.com/Pickupnaalden
Google+ : https://plus.google.com/+FCaris_pickupnaalden

KD-3033



SPECIFICATIONS

MOTOR and TURNTABLE

Drive System	Belt Drive System
Motor	4-pole Synchronous Motor (for turntable). 24-pole Synchronous Gear Motor (for automatic operation).
Turntable Platter	30 cm (12 ") diameter Aluminum Alloy Die-Cast
Speeds	2-Speeds, 33-1/3 and 45 rpm
Wow and Flutter	Less than 0.06% (WRMS)
Signal to Noise Ratio	More than 49 dB

TONEARM

Type	Static-Balance Type, S-Shaped Pipe Arm, with Lateral Balancer, EIA Plug-in Connector
Effective Arm Length	215 mm (8-7/16")
Over-Hang	9.5 mm (3/8")
Tracking Error	±1.5 degree
Stylus Force Variable Range	0 to 4 grams
Usable Cartridge Weight	4 to 13 grams

CARTRIDGE

Type	Moving Magnet Type [V-39 MKII]
Frequency Response	20 ~ 20,000 Hz
Channel Separation	More than 25 dB (1,000 Hz)
Output Voltage	3 mV (1,000 Hz, 5 cm/sec)
Output Balance	1.5 dB (1,000 Hz, 5 cm/sec)
Load Impedance	50 Kohms
Stylus	0.5 mil diamond
Stylus Force	2±0.25 grams
Compliance	7 × 10 ⁻⁶ cm/dyne
Replacement Stylus	N-39 MKII

MISCELLANEOUS

Power Requirements	○ AC 120V, 60Hz K.P ○ AC 220V, 50Hz L ○ AC 220 ~ 240V, 50Hz T.X.S ○ AC 110 ~ 120V/ 220 ~ 240V 50/60Hz M.U.W
Power Consumption	14 Watts
Dimensions	W 480 mm (18-29/32 ") D 350 mm (13-25/32 ") H 168 mm (6-5/8 ")
Weight	7 kg (15.4 lbs)

SPECIAL MECHANISM

(Additional Feature)	Auto-In Mechanism, Auto-Cut Mechanism, Auto-Return Mechanism, Auto-Repeat Mechanism, Manual Operating Mechanism, Disc Size Selector, Pause Elevation, Anti-Skating Device, Head Shell Stand, Insulator, Free-Stop Action Dust Cover, Low Capacity Audio Cord with PIN Plug, Pilot Lamp
-----------------------------	---

ACCESSORIES

(Supplied)	EP Adaptor Motor Lubricating Oil Over-Hang Gauge Motor Pulley and Screw Driver M U W
-------------------	--