



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : [www.pickupnaalden.com](http://www.pickupnaalden.com)  
Email : [info@pick-upnaalden.nl](mailto:info@pick-upnaalden.nl)  
Facebook : [www.facebook.com/pickupnaalden](http://www.facebook.com/pickupnaalden)  
Twitter : [twitter.com/Pickupnaalden](http://twitter.com/Pickupnaalden)  
Google+ : [https://plus.google.com/+FCaris\\_pickupnaalden](https://plus.google.com/+FCaris_pickupnaalden)

# KD-5033AF



## SPECIFICATIONS

### MOTOR and TURNTABLE

Drive System	Direct Center Drive System
Motor	8-pole 24 slot D.C. Servo Motor (for turntable), 24-pole Synchronous Gear Motor (for automatic operation)
Turntable Platter	30 cm (12") diameter Aluminum Alloy Die-Cast
Speeds	2-Speeds, 33-1/3 and 45 rpm
Speed Control Range	Within $\pm 3\%$ (individual control for 33 1/3 and 45 rpm)
Wow and Flutter	Less than 0.05% (WRMS)
Signal to Noise Ratio	More than 58dB

### TONEARM

Type	Static-Balance Type, S-Shaped Pipe Arm, with Lateral Balancer, EIA Plug-in Connector
Effective Arm Length	215 mm (8-7/16")
Over-Hang	9.5 mm (3/8")
Tracking Error	$\pm 1.5$ degree
Stylus Force Variable Range	0 to 4 grams
Usable Cartridge Weight	4 to 13 grams

### CARTRIDGE (V-46)

Type	Moving Magnet Type [V-46]
Frequency Response	10 ~ 25,000 Hz
Channel Separation	More than 25 dB (1,000 Hz)
Output Voltage	3 mV (1,000 Hz, 5 cm/sec)
Output Balance	1.5 dB (1,000 Hz, 5 cm/sec)
Load Impedance	50 Kohms
Stylus	0.5 mil diamond
Stylus Force	$2 \pm 0.25$ grams
Compliance	$10 \times 10^{-6}$ cm/dyne
Replacement Stylus	N-46

### CARTRIDGE (V-41A)

Type	V-shaped dual type (V-41A)
Frequency Response	20 ~ 20,000 Hz
Channel Separation	More than 25 dB (at 1,000 Hz)
Output Voltage	2 mV (5 cm/sec at 1,000 Hz)
Output Balance	1.5 dB (5 cm/sec at 1,000 Hz)
Load Impedance	50 k ohms
Stylus	0.6 mil diamond
Stylus Pressure	$2 \pm 0.5$ grams
Compliance	$7 \times 10^{-6}$ cm/dyne

### SPECIAL MECHANISM

(Additional Feature)	Stroboscope with Lamp, Fine Speed Adjusting Control, Auto-In Mechanism, Auto-Cut Mechanism, Auto-Return Mechanism, Auto-Repeat Mechanism, Manual Operating Mechanism, Disc Size Selector, Pause Elevation, Anti-Skating, Insulator, Head Shell Stand, Pilot Lamp, Free-Stop Action Dust Cover, Low Capacity Audio Cord with PIN Plug Level Indicator
----------------------	---

### ACCESSORIES

(Supplied)	EP Adaptor Over Hang Gauge
------------	-------------------------------

### MISCELLANEOUS

Power Requirement	AC 110 ~ 120V/ 220 ~ 240V, 50/60 Hz
Power Consumption	7 Watts
Dimensions	W 480 mm (18 7/8") D 350 mm (13.6 7/8") H 168 mm (6 5/8")
Weight	10 kg (22 lbs)