



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : www.pickupnaalden.com
Email : info@pick-upnaalden.nl
Facebook : www.facebook.com/pickupnaalden
Twitter : twitter.com/Pickupnaalden
Google+ : https://plus.google.com/+FCaris_pickupnaalden

KD-500 (KD-550)



Photo : KD-550

SPECIFICATIONS

MOTOR and TURNTABLE

Drive System	Direct drive system
Motor	8 pole 24 slot brushless DC servo motor
Turntable Platter	30 cm (12") diameter 1.5 kg (3.3 lbs.) weight Aluminum alloy die-cast
Speeds	2 speeds, 33-1/3 and 45 rpm
Speed Control Range	Within $\pm 8\%$ (Individual control for 33-1/3 and 45 rpm)
Wow and Flutter	Less than 0.03% (WRMS) DIN $\pm 0.05\%$
Signal to Noise Ratio (Rumble)	JIS Better than 60 dB DIN unweighted Better than -50 dB DIN weighted Better than -70 dB

TONEARM

Type	Static-balance type, S-shaped pipe arm, EIA plug-in connector
Effective Arm Length	237 mm (9-5/16")
Over-Hang	15 mm (9/16")
Tracking Error	± 1.5 degree
Stylus Pressure Variable Range	0 to 4 grams
Usable Cartridge Weight	5 to 12 grams (Supplied head shell 11 grams)

CARTRIDGE

Type	Moving magnet type (V-46)
Frequency Response	10 ~ 25,000 Hz
Channel Separation	Better than 25 dB (1,000 Hz)
Output Voltage	3 mV (1,000 Hz, 5 cm/sec.)
Output Balance	1.5 dB (1,000 Hz, 5 cm/sec.)
Load Impedance	50 k ohms
Stylus	0.5 mil diamond
Stylus Pressure	1.5 ± 0.5 grams
Compliance	10×10^{-6} cm/dyne
Replacement Stylus	N-46

MISCELLANEOUS

Power Consumption	9 watts
Dimensions	W 502 mm (19-3/4") D 382 mm (15") H 162 mm (6-3/8")
Weight	15.5 kg (34.2 lbs) KD-550 14.9 kg (32.8 lbs.) KD-500
Special Features	Stroboscope with lamp Fine speed adjusting control Anti-skating device (KD-550) Oil damped arm elevation (KD-550) Stylus pressure direct-readout counter (KD-550) Height adjusting insulation Free stop action dust cover Low capacity audio cord (KD-550) Head shell stand
Supplied Accessories	EP adaptor (with over-hang checker), Head shell Ground wire Hexagonal wrench Arm base (KD-500)