



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : [www.pickupnaalden.com](http://www.pickupnaalden.com)  
Email : [info@pick-upnaalden.nl](mailto:info@pick-upnaalden.nl)  
Facebook : [www.facebook.com/pickupnaalden](http://www.facebook.com/pickupnaalden)  
Twitter : [twitter.com/Pickupnaalden](http://twitter.com/Pickupnaalden)  
Google+ : [https://plus.google.com/+FCaris\\_pickupnaalden](https://plus.google.com/+FCaris_pickupnaalden)

## KP-1022



### SPECIFICATIONS

<b>Drive System:</b>	Belt drive system.
<b>Motor:</b>	4-pole Synchronous Motor.
<b>Turntable:</b>	12 inch (30 cm) diameter aluminum alloy die-cast,
<b>Speeds:</b>	2 Speeds, 33-1/3 and 45 rpm.
<b>Wow-Flutter:</b>	Less than 0.07%
<b>Signal to Noise Ratio:</b>	More than 47 dB.
<b>Tonearm:</b>	Static-Balance Type, S-Shaped Pipe Arm, EIA Plug-in Connector
<b>Tracking Error:</b>	±1.5 degree.
<b>Stylus Pressure Variable Range:</b>	0 to 4 grams.
<b>Usable Cartridge Weight:</b>	4 to 10 grams.
<b>CARTRIDGE</b>	
<b>Type:</b>	Moving Magnet Type (V-39 MK-II).
<b>Freq. Response:</b>	20 ~ 20,000 Hz.
<b>Channel Separation:</b>	More than 25 dB (1,000 Hz).
<b>Output:</b>	3 mV (1,000 Hz, 50 mm/sec).
<b>Output Balance:</b>	1.5 dB (1,000 Hz, 50 mm/sec).
<b>Load Impedance:</b>	50 k ohms.
<b>Stylus Pressure:</b>	2 ±0.25 grams.
<b>Stylus:</b>	0.5 mil diamond.
<b>Compliance:</b>	7 x 10 <sup>-6</sup> cm/dyne.
<b>Replacement Stylus:</b>	N-39 MK-II
<b>Special Mechanism:</b>	Variable Speed Pause Elevation. Anti-Skating Device. Stylus Pressure Direct-Readout Counter.
<b>Supplied Accessories:</b>	EP Adaptor, Motor Lubricating Oil, Over-Hang Gauge, Motor Pulley (except U.S.A. and Canada Market), Screw Driver (except U.S.A. and Canada Market).
<b>Power Consumption:</b>	11 watts.
<b>Dimensions:</b>	W 17-9/16" (446 mm), H 6-7/8" (175 mm), D 13-15/16" (354 mm).
<b>Weight:</b>	13.2 lbs (6 kg).