



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : www.pickupnaalden.com
Email : info@pick-upnaalden.nl
Facebook : www.facebook.com/pickupnaalden
Twitter : twitter.com/Pickupnaalden
Google+ : https://plus.google.com/+FCaris_pickupnaalden

KP-2021



SPECIFICATIONS

DRIVE: Belt Drive System, **MOTOR:** Outer-rotor hysteresis synchronous, **TURNTABLE:** 12 inch (30 cm) Solid die-cast, aluminum alloy type, **SPEED:** Two speed, 33-1/3 and 45 r.p.m., **WOW & FLUTTER:** Less than 0.08%, **SIGNAL TO NOISE RATIO:** More than 45 dB, **TONE ARM:** Static Balanced Pipe Arm, **TRACKING ERROR:** ± 1.5 degrees, **STYLUS FORCE VARIABLE RANGE:** 0 to 4 grams, **CARTRIDGE:** Moving Magnet Type, **FREQUENCY RESPONSE:** 20 to 20,000 Hz, **OUTPUT BALANCE:** within ± 1 dB, **CHANNEL SEPARATION:** More than 25 dB at 1,000 Hz, **IMPEDANCE:** 5 Kohms, **OUTPUT VOLTAGE:** 5 mV (1,000 Hz, 5 cm/sec.), **LOAD IMPEDANCE:** 50 Kohms, **RECOMMENDED STYLUS FORCE:** 3 ± 0.5 grams, **STYLUS:** 0.7 mil Diamond stylus, **COMPLIANCE:** 7×10^{-6} cm/dyne, **REPLACEMENT STYLUS:** Type N-34, **SPECIAL MECHANISM:** Oil damped arm elevation, **SUPPLIED ACCESSORIES:** EP Adaptor, Motor oil, **POWER REQUIREMENTS:** AC 110 ~ 120 V/220 ~ 240 V 50/60 Hz, **POWER CONSUMPTION:** 60 Hz 14W, 50 Hz 15.5W, **DIMENSIONS:** 6-1/2" (H) x 18-1/8" (W) x 16-1/8" (D), **WEIGHT:** 13.2 lbs.