



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : [www.pickupnaalden.com](http://www.pickupnaalden.com)  
Email : [info@pick-upnaalden.nl](mailto:info@pick-upnaalden.nl)  
Facebook : [www.facebook.com/pickupnaalden](http://www.facebook.com/pickupnaalden)  
Twitter : [twitter.com/Pickupnaalden](http://twitter.com/Pickupnaalden)  
Google+ : [https://plus.google.com/+FCaris\\_pickupnaalden](https://plus.google.com/+FCaris_pickupnaalden)

# KP-3021



## SPECIFICATIONS

<b>Drive</b>	Belt Drive System
<b>Motor</b>	Outer-rotor hysteresis synchronous
<b>Turntable</b>	12 inch (30 cm) Solid die-cast aluminum alloy type
<b>Speed</b>	Two Speed, 33-1/3 and 45 rpm
<b>Wow and Flutter</b>	Less than 0.08%
<b>Signal to Noise Ratio</b>	More than 45 dB
<b>Tonearm</b>	Static Balance Pipe Arm, 4-terminal plug-in type, Lateral Balancer
<b>Tracking Error</b>	$\pm 1.5$ degrees
<b>Stylus Pressure Variable Range</b>	0 to 4 grams
<b>Cartridge</b>	Moving Magnet type
<b>Frequency response</b>	20 to 2,000 Hz
<b>Output balance</b>	Within $\pm 1$ dB
<b>Channel separation</b>	More than 25 dB at 1,000 Hz
<b>Impedance</b>	5k ohms
<b>Output voltage</b>	5 mV (1,000 Hz, 5 cm/sec)
<b>Load impedance</b>	50k ohms
<b>Recommended stylus pressure</b>	$3 \pm 0.5$ grams
<b>Stylus</b>	0.7 mil Diamond Stylus
<b>Compliance</b>	$7 \times 10^{-6}$ cm/dyne
<b>Replacement stylus</b>	TYPE N-34
<b>Special Mechanism</b>	Auto-in-Auto-cut, Auto-return, Auto-repeat, disc size selector manual-in system, 24 pole synchronous gear motor for arm drive
<b>Supplied Accessories</b>	Plug-in head, EP Adaptor, Motor oil
<b>Power Requirements</b>	AC 110 ~ 120V/220 ~ 240V, 50/60 Hz
<b>Power Consumption</b>	60 Hz 14W, 50 Hz 15.5W
<b>Dimensions</b>	H 17" (175) $\times$ W 18-1/8" (460) $\times$ D 16-1/8" (410) (mm)
<b>Weight</b>	14.3 lbs.