



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : [www.pickupnaalden.com](http://www.pickupnaalden.com)  
Email : [info@pick-upnaalden.nl](mailto:info@pick-upnaalden.nl)  
Facebook : [www.facebook.com/pickupnaalden](http://www.facebook.com/pickupnaalden)  
Twitter : [twitter.com/Pickupnaalden](http://twitter.com/Pickupnaalden)  
Google+ : [https://plus.google.com/+FCaris\\_pickupnaalden](https://plus.google.com/+FCaris_pickupnaalden)

# KP-5021



## SPECIFICATIONS

<b>Drive</b>	Belt and Idler Wheel, Dual-Drive System
<b>Motor</b>	4-pole Synchronous Motor
<b>Turntable</b>	12-9/16 inch (32 cm) Solid die-cast aluminum alloy type, weighing 4.4 lbs.
<b>Speed</b>	Two Speed, 33-1/3 and 45 rpm
<b>Wow and Flutter</b>	Less than 0.05%
<b>Signal to Noise Ratio</b>	More than 50 dB
<b>Tonearm</b>	Static Balanced Pile Arm. Direct Reading Stylus Pressure, 4-terminal plug-in type, Lateral Balancer, Inside Force Cancellor.
<b>Tracking Error</b>	±1 degree
<b>Stylus Pressure Variable Range</b>	0 to 4 grams
<b>Cartridge</b>	Vertical Magnet type
<b>Frequency response</b>	10 to 20,000 Hz
<b>Output Balance</b>	Within ±1 dB
<b>Channel separation</b>	More than 25 dB at 1,000 Hz
<b>Impedance</b>	5.5k ohms
<b>Output voltage</b>	5 mV (1,000 Hz, 5 cm/sec)
<b>Load impedance</b>	50k ohms
<b>Recommended stylus pressure</b>	2.5 ± 0.5 grams
<b>Stylus</b>	0.7 mil Diamond Stylus
<b>Compliance</b>	10 × 10 <sup>-6</sup> cm/dyne
<b>Replacement stylus</b>	Type N-33
<b>Special Mechanism</b>	One touch 50 ~ 60 Hz changeover mechanism; Lever controlled oil damped arm elevation, AC ON/OFF-Idler OFF mechanism.
<b>Supplied Accessories</b>	Spare plug-in Head, EP Adaptor, Grease Tube for Idler, small screwdriver, Lubricating Oil.
<b>Power Requirement</b>	AC 110 ~ 120V/220 ~ 240V, 50/60 Hz
<b>Power Consumption</b>	60 Hz 14W, 50 Hz 15.5W
<b>Dimensions</b>	Width 16-1/8" × Height 7" × Depth 16-1/8"
<b>Weight</b>	24.2 lbs.