



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : www.pickupnaalden.com
Email : info@pick-upnaalden.nl
Facebook : www.facebook.com/pickupnaalden
Twitter : twitter.com/Pickupnaalden
Google+ : https://plus.google.com/+FCaris_pickupnaalden

PC-200U



SPECIFICATIONS

MOTOR:	4-pole Synchronous motor.
DRIVING METHOD:	Rim Drive
TURNTABLE:	12 inches Die-cast Aluminum-alloy.
SPEEDS:	Two-speeds, 33-1/3 and 45 rpm.
WOW FLUTTER:	Less than 0.2%
SIGNAL TO NOISE RATIO:	More than 40 dB.
TONE ARM:	Static Balanced pipe Arm. Accepts 4-prong Plug-in Heads.
CARTRIDGE:	Moving Magnet Type
FREQUENCY RESPONSE:	20 to 20,000 Hz
CHANNEL SEPARATION:	More than 25 dB
IMPEDANCE:	5 kohms at 1,000 Hz
OUTPUT VOLTAGE:	5 to 8 mV (1,000 Hz 5 cm/sec)
TRACKING FORCE:	3 to 4 grams
STYLUS:	0.7 mil diamond
COMPLIANCE:	8×10^{-6} cm/dyne
POWER:	115V/230V 50/60Hz. AC at 15VA
DIMENSIONS:	Width $18\frac{2}{5}$ inches Height 8 inches Depth $16\frac{2}{5}$ inches
WEIGHT:	9.1 kg (20 Lbs)