



Deze download wordt u gratis aangeboden door Pick-upnaalden.nl

Web : www.pickupnaalden.com
Email : info@pick-upnaalden.nl
Facebook : www.facebook.com/pickupnaalden
Twitter : twitter.com/Pickupnaalden
Google+ : https://plus.google.com/+FCaris_pickupnaalden

PC-350



SPECIFICATIONS

| | |
|---------------------------------|---|
| DRIVE: | Belt and Idler Wheel, Dual-Drive System. |
| MOTER: | 4-pole Synchronous Motor |
| TURNTABLE: | 32cm (12½") soled die-cast aluminum alloy type. Weight 4.4 lbs. |
| SPEED: | Two speed, 33⅓ and 45 rpm. |
| POWER REQUIREMENT: | 12 watts at 50 Hz, 11 watts at 60 Hz. |
| WOW-FLUTTER: | Less than 0.04% |
| SIGNAL TO NOISE RATIO: | Sample Value: Less than 45 dB, Spec. Value: Less than 43 dB. |
| TONE ARM: | Direct Reading Stylus Pressure, Static Balanced Pipe Arm. 4 terminal Plug-in Head type. |
| STYLUS PRESSURE VARIABLE RANGE: | 0 to 4 grams |
| RECOMMENDED STYLUS PRESSURE: | 2 to 3 grams |
| CARTRIDGE: | Moving Magnet type |
| OUTPUT BALANCE: | Within 2.5 dB at 1,000 Hz |
| CHANNEL SEPARATION: | More than 15 dB at 1,000 Hz |
| OUTPUT VOLTAGE: | 5~8 mV (1,000 Hz 5 cm/sec) |
| STYLUS: | 0.7 mil Diamond Stylus |
| COMPLIANCE: | 15 × 10 ⁻⁶ cm/dyne |
| REPLACEMENT STYLUS: | Type N-23 |
| LEVER OPERATION MECHANISM: | Oil Damped Arm Elevation, AC ON/OFF, Idler Control |
| DIMENSIONS: | Width 18⅛" × Height 7" × Depth 16¼" |
| WEIGHT: | 23.3 lbs. |